

SyncroMNC-LR

Moving Nozzle Controller


The Syncronorm MNC is intended to control single Moving Nozzles and 2D Fountain Nozzles. The Moving Nozzle Controller can be used in center sensor or in end sensor mode (separate selectable personalities).

Fully DMX RDM compatible with Syncronorm hardware. All settings are set remotely via the Depence Software DMX RDM tool and are stored in non volatile Memory.



Features

- ✓ 1-Axis Controlable
- ✓ Four RDM personality settings
- ✓ 2 Sensor inputs (information about the type sensor you are using is required before)
- ✓ 4x Control Outputs 24V DC
- ✓ Syncronorm RDM Browser compatible



**made
in
Germany**

Technical Details

	SyncroMNC-LR
Dimensions	160x90x58mm DIN Rail 6.5U
Weight	0.33 kg
Protection Class	IP20
Power Supply	24V DC
Operation Temperature	0..40°C/0..80% humidity
Certification	CE
Outputs	4x Control Outputs 24V DC
Inputs	DMX512/1990, DIN 56930-2, DMX512-A, ANSI E1-20 DMX RDM 2x Sensor Inputs
Order Number	SN-STMNCLR

NOTE: This unit requires the SyncroTools DMX address board (Order number: SN-STADRB)

Syncronorm GmbH

Graf-Gottfried-Strasse 122
D-59755 Arnsberg
Phone: +49(0) 2932 - 89786 0
Fax: +49(0) 2932 - 89786 299
Web: www.syncronorm.de
E-mail: info@syncronorm.de

CEO: C.Schmelzer & T.Franke

Bank Details

Volksbank Hellweg eG
Westenhellweg 1
59494 Soest

Account: 501 600 1000
IBAN: DE12 4146 0116 5016 0010 00
BIC/SWIFT: GENODEM1SOE

Tax Information

USt. / VAT ID: DE251724916
TAX No: 343/5749/0291

Registered at:
Amtsgericht Arnsberg
HRB: 7698

Brands

