

SyncroNode

Ethernet DMX-RDM Node


The SyncroNode offers 4 DMX-RDM outputs via ArtNET 1,2,3,4 or sACN. The Ethernet to DMX converter is optimally suited for power and signal distribution systems.

Power supply is via PoE (Power over Ethernet conforming to standard IEEE 802.3af-2003) or external PSU 24VDC (not included with delivery). The converter can easily be configured via the internal Web server. This allows you to select the protocol used, configure the DMX outputs and assign the Net- and Sub-Nets to the outputs.



Features

- ✓ Ethernet to DMX-RDM Converter
- ✓ 4x DMX-RDM Universes
- ✓ Supports POE (Power over Ethernet)
- ✓ ArtNET and sACN compatible
- ✓ Configuration via Webbrowser
- ✓ Extension for V:Server



Technical Details

	SyncroNode DMX/RDM
Dimensions	100x90x58mm DIN Rail 5U
Weight	0.33 kg
Protection Class	IP20
Power Supply	24V DC
Operation Temperature	0..40°C/0..80% humidity
Certification	CE
Outputs	4 Outputs DMX512/1990, DIN 56930-2, DMX512-A, ANSI E1-20 DMX RDM
Inputs	RJ45 Ethernet ArtNET Ver. 1, 2, 3, 4 & sACN
Order Number	SN-STNODE

Syncronorm GmbH

Graf-Gottfried-Strasse 122
D-59755 Arnsberg
Phone: +49(0) 2932 - 89786 0
Fax: +49(0) 2932 - 89786 299
Web: www.syncronorm.de
E-mail: info@syncronorm.de

CEO: C.Schmelzer & T.Franke

Bank Details

Volksbank Hellweg eG
Westenhellweg 1
59494 Soest

Account: 501 600 1000
IBAN: DE12 4146 0116 5016 0010 00
BIC/SWIFT: GENODEM1SOE

Tax Information

USt. / VAT ID: DE251724916
TAX No: 343/5749/0291

Registered at:
Amtsgericht Arnsberg
HRB: 7698

Brands

